

Amendments to the Claims:

1. (Currently Amended) An automated packaging apparatus for depositing a predetermined number of pills into a series of containers, comprising:

one or more ~~a plurality of~~ rotary slats, wherein each of said ~~plurality of~~ rotary slats is independently rotatable and comprises an outer peripheral edge portion, said outer peripheral edge portion of each rotary slats ~~are configured such that said outer peripheral edge portions together define~~ defining a common interior space, each of said outer peripheral edge portions defining a plurality of pill apertures extending therethrough, and each ~~of said pill apertures is of a~~ respective one of said slats being configured to receive one of the pills from said common interior space of said respective slat at a first position and transmit the pill outside said respective rotary slats at a second position, each of said pill apertures of said respective slat being disposed in a single row for depositing pills into one of the containers;

a conveyor configured to move a plurality of open containers along a predetermined path of travel and position each of said containers adjacent said a respective rotary slat to define a delivery path extending between the second position of said rotary slat and said container;

at least one drive motor in driving engagement with each of said rotary slats for rotating each of said rotary slats; and

a controller connected to said at least one drive motor for controlling said at least one drive motor such that each of said rotary slats can be independently rotated for different durations.

2. (Currently Amended) The automated packaging apparatus of Claim 1 further comprising a shroud extending from a location proximate to said first position to a location proximate to said second position such that said shroud prevents the pills from exiting each of said rotary slats through said pill apertures prior to the pills reaching said second position.

3. (Currently Amended) The automated packaging apparatus of Claim 1 further comprising an air blower located in said common interior space of each rotary slat and configured to emit air towards said pill apertures at said second position.

4. (Currently Amended) The automated packaging apparatus of Claim 1 further comprising at least one ~~a plurality of~~ plows, each plow extending toward said pill apertures at the second position of said respective rotary slats such that said plows urge said pills from said pill apertures.

5. (Currently Amended) The automated packaging apparatus of Claim 1 further comprising an air blower located outside each of said ~~plurality of~~ rotary slats and configured to emit air towards said pill apertures at a third position of said respective rotary slats such that pills positioned within said pill apertures of said respective rotary slat at said third position are urged into said common interior space of said respective rotary slat.

6. (Currently Amended) The automated packaging apparatus of Claim 1 wherein each of said ~~plurality of~~ rotary slats defines an inner contour sloped toward said pill apertures to facilitate the entry of pills into said pill apertures.

7. (Original) The automated packaging apparatus of Claim 1 wherein said pill apertures are slanted downward toward the outside of said rotary slats when positioned at the second position such that said pills tend to fall from said pill apertures and out of said rotary slats at the second position.

8. (Currently Amended) The automated packaging apparatus of Claim 1 wherein said inner surface of each of said ~~plurality of~~ rotary slats defines an inner contour that varies around the circumference of the rotary slat to facilitate the entry of pills into said pill apertures.

9. (Original) The automated packaging apparatus of Claim 1 wherein said rotary slats are supported by a plurality of cradle rollers.

10. (Original) The automated packaging apparatus of Claim 1 further comprising a drive assembly engaged to said rotary slats for independently rotating each of said rotary slats.

11. (Original) The automated packaging apparatus of Claim 10 wherein said drive assembly includes a plurality of drive wheels, each said drive wheel contoured to match said outer peripheral edge portion of said rotary slats.

12. (Original) The automated packaging apparatus of Claim 1 wherein said rotary slats are positioned with gaps of between about 0.5 to 1 millimeter between adjacent rotary slats.

13. (Original) The automated packaging apparatus of Claim 1 wherein said rotary slats are formed of a compound comprising acrylonitrile-butadiene-styrene and polytetrafluoroethylene.

14. (Original) The automated packaging apparatus of Claim 1 further comprising a reservoir configured to hold the pills and feed the pills into said common interior space defined by said rotary slats.

15. (Currently Amended) The automated packaging apparatus of Claim 12 further comprising a reservoir gate configured to control the passage of pills from said reservoir to said common interior space of each rotary slat.

16. (Currently Amended) The automated packaging apparatus of Claim 1 further comprising a sensor configured to detect the quantity of the pills in said common interior space of said each rotary slats.

17. (Original) The automated packaging apparatus of Claim 1 further comprising a plurality of chutes, each of said chutes defining said delivery path extending from said second position of one of said rotary slats to the corresponding container.

18. (Original) The automated packaging apparatus of Claim 1 further comprising a delivery sensor that detects the delivery of a pill through said delivery path.

19. (Original) The automated packaging apparatus of Claim 1 wherein said controller is configured to alternately accelerate and decelerate said rotary slats such that said rotatary slats are vibrated and the pills are agitated.

20. (Currently Amended) A method of depositing a predetermined number of pills into a series of containers, comprising:

disposing a plurality of pills in ~~a common~~ an interior space of ~~a drum, the drum~~
~~comprising each of one or more a plurality of~~ rotary slats;

capturing a plurality of the pills in individual pill apertures defined by an outer peripheral edge portion of ~~the plurality of each~~ rotary slats;

independently rotating the rotary slats to a position where the pills are released from the pill apertures thereby delivering the pills to a plurality of containers;

counting each pill as the pills are delivered to the containers;

positively determining the number of pills deposited into each of the containers; and

stopping the rotation of the rotary slats for which the respective containers have received a predetermined number of pills while continuing the rotation of any slats for which the respective container has not received the predetermined number of pills.

21. (Currently Amended) The method of Claim 20 further comprising directing air toward the pill apertures in a direction from the ~~common~~ interior space of ~~the~~ each rotary slats toward the outside of the rotary slats to facilitate the release of the pills from the pill apertures.

22. (Original) The method of Claim 20 further comprising contacting the pills with a plow to urge the pills from the rotary slats.

23. (Currently Amended) The method of Claim 20 further comprising directing air toward the pill apertures in a direction from the outside of a respective one of the rotary slats to urge pills in the pill apertures toward the ~~common~~ interior space of the respective rotary slat.

24. (Currently Amended) The method of Claim 20 further comprising detecting the quantity of the pills in ~~the common~~ the interior space of each rotary slat and automatically feeding more pills into the ~~common~~ interior space to maintain a predetermined quantity of pills in the ~~common~~ interior space.

25. (Original) The method of Claim 20 wherein said rotating step comprises alternately accelerating and decelerating the rotary slats to agitate the pills.

26. (Original) The method of Claim 20 further comprising during said rotating step preventing the release of each of the pills from the pill apertures before each of the pills reaches a predetermined release position with a shroud that partially surrounds the rotary slats.

27. (Original) The method of Claim 20 further comprising supporting the rotary slats with at least two cradle rollers.

28. (Original) The method of Claim 20 further wherein said rotating step comprises independently driving each of the rotary slats with at least one drive device.

29. (Original) The method of Claim 20 wherein said delivering step comprises dropping the pills through chutes, the chutes guiding the pills toward the containers.